

MEDIUM DUTY – 750N



HP Flex™ Pliable PVC Corrugated Conduit

Conforms to AS/NZS 2053.5-2001

Properties

Material	uPVC
Colour	Grey
Duty Rating	Medium Duty – MD
UV Resistance	Extreme UV (T) Stabilised
Resistance to compression	750 N / 5cm
Resistance to impact	2 Joule
Maximum Temperature	+60°C
Minimum Temperature	-5°C
IP Ingress Protection	IP66
Dielectric Strength	Electro-insulating
B.E.P Certified	Yes
Resistance to flame propagating	Non-flame propagating (UL94-V0)
Lead Free	Yes
RoHS Compliance	Heavy Metals Free (RoHS)
Rodent Repellent	Not attractive to rodents



**MANUFACTURED
IN AUSTRALIA**

Conforms to AS/NZS 2053.5-2001

**EXTREME
UV (T) STABILISED**



**B.E.P
CERTIFIED**



**2 JOULE
IMPACT RESISTANCE**



**750N/5CM
COMPRESSION RESISTANCE**



**CONFORMS TO
AS/NZS 2053.5-2001**



HP Flex™ Medium Duty PVC Corrugated Conduit is ideal for indoor or outdoor static installations. Its high UV stabilisation makes it suitable for residential or industrial installations. Conforming to AS/NZS 2053.5-2001, **HP Flex™** has a 25 year manufacturing warranty.

MEDIUM DUTY – 750N

Part Number	Description
HPPCM16/10	MD Corrugated Conduit Roll 16mm x 10m
HPPCM16/20	MD Corrugated Conduit Roll 16mm x 20m
HPPCM16/50	MD Corrugated Conduit Roll 16mm x 50m
HPPCM20/10	MD Corrugated Conduit Roll 20mm x 10m
HPPCM20/20	MD Corrugated Conduit Roll 20mm x 20m
HPPCM20/50	MD Corrugated Conduit Roll 20mm x 50m
HPPCM25/10	MD Corrugated Conduit Roll 25mm x 10m
HPPCM25/20	MD Corrugated Conduit Roll 25mm x 20m
HPPCM25/50	MD Corrugated Conduit Roll 25mm x 50m
HPPCM32/10	MD Corrugated Conduit Roll 32mm x 10m
HPPCM32/25	MD Corrugated Conduit Roll 32mm x 25m
HPPCM40/10	MD Corrugated Conduit Roll 40mm x 10m
HPPCM40/25	MD Corrugated Conduit Roll 40mm x 25m
HPPCM50/10	MD Corrugated Conduit Roll 50mm x 10m
HPPCM50/25	MD Corrugated Conduit Roll 50mm x 25m
HPPCM63/10	MD Corrugated Conduit Roll 63mm x 10m

PART NUMBER	OUTSIDE DIAMETER (mm)	INSIDE DIAMETER (mm)	LENGTH* (M)
HPPCM16	16 (+0, -0.3)	10.7	10, 20, 50
HPPCM20	20 (+0, -0.3)	12.7	10, 20, 50
HPPCM25	25 (+0, -0.4)	16.5	10, 20, 50
HPPCM32	32 (+0, -0.4)	22	10, 25
HPPCM40	40 (+0, -0.4)	28.3	10, 25
HPPCM50	50 (+0, -0.5)	36	10, 25
HPPCM63	63 (+0, -0.6)	46	10

***Custom lengths available**